



III Ciclo de 20 MasterClass

AGUASRESIDUALES.INFO

MASTERCLASS 08



“Alternativas a los tratamientos biológicos convencionales de la EDAR.”

Oriol Carbó

Técnico de I+D+i en GS INIMA



**Ciclo de 20
MasterClass**
AGUASRESIDUALES.INFO

Jueves

22 MAYO

16:30h. España

- **Empresa con una posición sólida en la industria de tratamiento de agua en todo el mundo**
- Más de 60 años en el mercado:



➤ 1968 Primera planta desaladora del mundo por ósmosis inversa en Cabo Verde

➤ 1970 Primera desaladora en España (Lanzarote)

➤ 2009 Mayor planta de secado térmico en España: Metrofang

➤ 2011 Mayor planta de biofiltración de Europa: E.D.A.R. Lagares

- Actúa en todas las fases de los proyectos : **Financiación, Ingeniería, Suministro, Construcción, Operación y Mantenimiento**
- Posicionada como una de las empresas con mayor número de plantas en modalidad concesional

GS INIMA ENVIRONMENT. PRESENCIA MUNDIAL



GSi - INNOVAMOS PARA NUESTROS CLIENTES

GSi cuenta con un equipo cualificado para investigar, proponer y pilotar proyectos innovadores y diferenciadores, con el **objetivo de ser más eficientes y competitivos**.



FOWE® en IDAM de Alicante II



OSCAR en EDAR Numancia de la Sagra



PRONOX® en EDAR La Garriga



PROGRAMOX® en EDAR La Garriga



ROWSIP® en IDAM de Ensenada (México)

MICROPLÁSTICOS

Uso de microorganismos específicos para la biodegradación de microplásticos en una EDAR

ROWSIP®

"Reverse Osmosis With Simple Intake and Pretreatment"
(Instalado en Desaladora Ensenada)

OSCAR

Oxidación Húmeda de la materia orgánica de fangos de depuración

DC-SOIAS

Desionización capacitiva de salmueras de plantas desaladoras

FOWE®

Recuperación de energía de la salmuera de una planta de desalación de agua de mar a través de membranas de ósmosis de directa

PRONOX®

Bases de diseño y control del proceso HRAS, como tratamiento previo a los Lodos Activos, en sustitución de la decantación primaria

PROGRAMOX®

Diseño y desarrollo de un prototipo de reactor Anammox a escala semi-industrial para operar a continuación de los procesos HRAS y AGS en la línea de agua

GEMELO DIGITAL

Optimización de las plantas de tratamiento a través de la inteligencia artificial mediante el desarrollo de un Gemelo Digital cognitivo


PROGRAMOX

by **GS Inima**

MasterClass
patrocinada por:

SMALLOPS
Sustainable nanoenergy

- ✓ Marca registrada
- ✓ Patente



Desarrollado conjuntamente con



lequia ECO-INNOVATIVE
ENVIRONMENTAL
SOLUTIONS
UdG

**Universitat
de Girona**

INDEX

1. Introduction

2. Objectives

3. Methodology

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX[®] vs. CAS

8. General conclusions

1. INTRODUCTION

2. Objectives

3. Methodology

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS


5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX® vs. CAS

8. General conclusions

Conventional WWTPs



- **PS + CAS**-based configurations predominate
- **AD** to produce CH_4

- **Energy consumption** (aeration, pumping, etc.)
- **Energy recovery** (CH_4 cogeneration)

Energy consumption in WWTPs

Specific treatment consumption:

- Catalonia: **0.452 kWh/m³** (ACA, 2021)
- World: **0.3-0.6 kWh/m³** (Wan et al., 2016)

WWTPs consumption vs. country electricity consumption (USEPA, 2007):


- United States: **3%**
- Others: up to **5%**

❑ **2/3** for **COD** oxidation


❑ **1/3** for **N** oxidation

❖ Efficient approach: **aeration reduction**

- Energy consumption distribution in a standard **CAS**-based WWTP:



Energy recovery in WWTPs



(Henze et al., 2008)

(Tchobanoglous et al., 2014)


(Heidrich et al., 2011)

- **Feasible recovery: 0.22 kWh/m³**
(i.e., 49% of consumption –0.45 kWh/m³–)

- **How can energy recovery be enhanced?**

- Mainstream AD
- Increase COD redirection to AD

Mainstream anaerobic membrane bioreactor (AnMBR)



Liu et al. (2014)


PROS

- ✓ Direct anaerobic COD conversion to CH_4

CONS

- Dissolved CH_4 in the effluent (50% of the produced CH_4)
- High energy filtration cost
- AD effluent with (high) soluble COD

COD redirection to AD: chemically enhanced primary treatment (CEPT)



- Chemical process, no biological activity

PROS


- ✓ High removal efficiency:
70-80% COD, 90% TSS, 90% P
(Diamantis et al., 2011)

CONS

- Addition of chemical products
- High volume of sludge

COD redirection to AD: High-rate activated sludge (HRAS)

(Canals et al., 2023)



- Biological process, but:
High load & low SRT
☐ $\text{HRT} < 1 \text{ h}$, $\text{SRT} < 1 \text{ d}$
Low DO consumption
☐ $0.5 - 1.0 \text{ mg DO/L}$
- Based on **sorption** and **bioaccumulation** rather than oxidation


PROS

- ✓ No chemical products addition
- ✓ Higher COD removal (55-65%) than PS (30-40%)
- ✓ Colloidal COD removal

CONS

- Lower COD removal than CEPT (55-65% vs. 80-90%)
- Fraction of COD oxidation (but small)

COD redirection + nutrient removal: A/B process



B-stage:

- Different configurations based on CAS
- Low influent COD
- Enough SRT to achieve BNR (N, P)

Problem: COD/N too low for denitrification



Alternative CAS: aerobic granular sludge (AGS)

- Developed lab-scale in **1990s** (*Morgenroth et al., 1997*)
- Real implementation in **2006**, Nereda® (*Pronk et al., 2017*)


Characteristics (*de Kreuk et al., 2007*):

- Minimum diameter of 0.2 mm
 - $SVI_{10}/SVI_{30} \approx 1.0$
 - Nitrifiers grow on granule surface
 - Polyphosphate accumulating organisms (PAO) grow inside the granules
- Sequencing batch reactor (**SBR**) operation
- ✓ **Lower footprint**
Fast-settling and high-thickening properties eliminates the need for secondary clarifiers
- ✓ **Lower energy consumption**
Recycling flows and mixers avoided

Pronk et al., 2020



HRAS + AGS



Novel approach


- AGS at low organic loading rate (OLR) (*Pronk et al., 2015*)
- HRAS+AGS only one recent lab-scale study available (*Kosar et al., 2023*)

- Potential difficulties in heterotrophic denitrification (A/B problem)

✓ Niche for **mainstream autotrophic N removal**

Nitrogen removal

Predominates in CAS and AGS



Process	Nitrification		Denitrification	
	O_2 demand (g O_2 /g N)	COD demand (g O_2 /g N)	O_2 balance (g O_2 /g N)	
Conventional nitrification – denitrification	4.57	2.86	1.71	
Nitritation – denitritation (via nitrite)	3.43	1.71	1.72	
PN-anammox	1.72	0	1.72	

AOB: ammonium oxidising bacteria


NOB: nitrite oxidising bacteria

het.: heterotrophic denitrifiers


anammox: anaerobic ammonium oxidation

○ If COD available, O_2 requirements are similar

○ If **COD not available** (A-B process), **PN-anammox** suitable
partial nitritation (PN) – anammox; **PN-anammox**; PNA;
autotrophic N removal



Mainstream autotrophic N removal: partial nitrification anammox (PNA)




Separated control of the PN and anammox processes

Not fully implemented yet

Literature
review

	Scale	PNA configuration	Problem for implementation
<i>Hausherr et al., 2022</i>	Pilot-scale	Two-stage	• Unknown NOB repression mechanism
<i>Pedrouso et al., 2023</i>	Pilot-scale	Two-stage	• Lack of long-term stability demonstration
<i>Podmirsed et al., 2022</i>	Full-scale	One-stage	• Constant sidestream anammox inoculation • Costly hydrocyclones
<i>Cao et al., 2017</i>	Full-scale	One-stage	• Only at 30°C

HRAS + two stage PNA (with AGS): process proposal



HRAS

- Already implemented; stable process

PN-AGS

- Few lab-scale studies combining AGS with COD removal and PN (Zhao et al., 2023)

anammox

- Effluent quality needs to be assessed

1. Introduction

2. OBJECTIVES

3. Methodology

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS


5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX® vs. CAS

8. General conclusions

- ❖ Study a new **mainstream configuration** for urban WWTPs: HRAS + PN-AGS + anammox (**PROGRAMOX®**)



1) Identify a suitable strategy to **achieve AGS**

2) **Achieve partial nitrification** with AGS

3) **Control** and **performance** of the combined PN-AGS + anammox process

4) **Energy balance** to compare PROGRAMOX® vs. La Garriga CAS

1. Introduction

2. Objectives

3. METHODOLOGY

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS


5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent


7. Energy balance: PROGRAMOX[®] vs. CAS

8. General conclusions


HRAS + PN-AGS + anammox mainstream pilot plant



- **Location:** La Garriga WWTP
(conventional WWTP near Barcelona)
- **Influent:** raw pretreated wastewater (before PS)
- No temperature control (water **12-28 °C**)



HRAS reactor



High load

- HRT 1 hour
- 2 g TSS/L
- SRT < 1 day

Low O₂ consumption


- 0.5 mg DO/L



- No inoculum


PN-AGS REACTOR

□ SBR at constant volume



- Volume exchange ratio (VER): 50 – 60 %
- 1.5 m³/d, HRT 12-13 h
- Aeration (fine+coarse): 2.0 mg DO/L


Inoculum: **floccular** activated sludge




Height 4.5 m (H/D = 9)

Anammox reactor

Continuous stirred tank reactor (**CSTR**)
with **baffle settler**:



- **1.5 m³/d, HRT 5 h**
- **Inoculum:** one-stage sidestream granular PNA biomass from Paques®
- **5 months** acclimation period
- Reactor solids content ca. **10 g VSS/L**



Analytical methods and sampling

- **Composite 24h samples** with automatic samplers (AS950, Hach):
Influent and effluent samples. Once/twice a week
- **Spot samples:**
Reactor's samples. Several times a week
- **TSS, VSS, SVI** and **alkalinity**: standard methods (APHA et al., 2017)
- **Anions** and **cations**: ion chromatography (ICS-5000, Dionex) and Hach Test N Tube (TNT) kits.
- **COD**: closed reflux and colorimetric method (Hach TNT kits)
- **Sludge size distribution**: sieving method (*van Loosdrecht et al., 2016*)
- **Sludge morphology**: stereomicroscope (Stereo Discovery V12, Zeiss)



1. Introduction

2. Objectives

3. Methodology

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX[®] vs. CAS

8. General conclusions

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS


6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX® vs. CAS

Motivation




Process
assessment




Identify a suitable strategy to **achieve AGS** from HRAS effluent (i.e., low COD and OLR)

AGS biomass waste strategies in views of granulation


a) Fill/draw waste →



b) Intense lateral waste →



c) Selective waste →



Operational periods


- ❖ 3 periods with 3 granulation strategies

Period	Biomass waste strategy	Day (d)	Cycle time (min)
I	(a) fill/draw	0 - 300	160 - 180
II	(b) intense lateral	301 - 458	180
III	(c) selective	459 - 781	180 - 360

- **Period III**, cycle time extended for **nitrification** purposes

4. AEROBIC GRANULATION FROM HRAS

Evolution of COD and OLR




- ✓ AGS influent COD **391 ± 84 mg/L**
- ✓ AGS effluent COD **74 ± 30 mg/L**

- OLR **1.6 ± 0.4 kg/(m³·d)** until day 600th

- From day 600th OLR **0.7 ± 0.7 kg/(m³·d)**

Evolution of the reactor TSS and biomass settleability

● TSS ○ SVI ■ Temperature



P-I

Days	TSS (g/L)	SVI (mL/g)
0 - 150	2.9 ± 0.6	116 ± 23 mL/g
150 - 220	up to 8.4 g/L as low as 29 mL/g	
220 - 300	2.0 g/L	86 mL/g


P-II

- TSS **1.0 ± 0.6 g/L**
- SVI from 20 to 160 mL/g

P-III

- TSS up to **14 g/L** with SVI of **20 mL/g** on day 540th, then gradual TSS reduction and SVI increase

Biomass fractions size distribution




➡ **Periods I & II:** coexistence of big aggregates (> 2.0 mm) and flocs (< 0.2 mm)

➡ **Period III:** appearance of granular fractions (0.2 < TSS < 2.0 mm)


4. AEROBIC GRANULATION FROM HRAS

Microscope observations

PERIOD I: day 200th




3000 µm



500 µm

PERIOD II: day 344th




1000 µm




1000 µm

4. AEROBIC GRANULATION FROM HRAS

PERIOD III: day 512th




5000 µm




500 µm

PERIOD III: day 539th




1000 µm




500 µm

4. AEROBIC GRANULATION FROM HRAS

PERIOD III: day 562th




1000 μm




500 μm

PERIOD III: day 596th



1000 μm



500 μm



Conclusions

- ✓ Rather stable AGS **influent** (HRAS effluent) **COD** of **391 ± 84 mg/L** was observed
- ✓ Suitable strategy to achieve AGS from HRAS effluent:
Selective wasting from the top of the settled sludge bed
- ✓ **Full granulation not crucial**
Low SVI (< 100 mL/g, densified biomass) helpful enough for an operation with COD removal

RESULTS AND DISCUSSION


4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent


7. Energy balance: PROGRAMOX® vs. CAS

Motivation




Achieve stable PN: effluent with NO_2^- and NH_4^+ (without NO_3^-), NOB repression/washout

Evolution of the SRT in the PN-AGS



- P-I SRT of 4 ± 3 days
- P-II SRT of 1 ± 0.3 day
- P-III SRT > 20 days until day 720th, when it was controlled at **10 days**


N-species and N removal in the PN-AGS



- NH_4^+ oxidation to NO_2^- (nitritation) in Periods I and III, when SRT is high enough. **No NO_3^- presence**
- Significant **N removal** in the PN-AGS. PI **57±15%** (flocs); PIII **37±16%** (AGS)

Which is the drive for PN?

Representative SBR cycle (Day 778th, Period III)



- Partial NH_4^+ oxidation without observed NO_3^- (i.e., **PN**)
- FNA** values from 0.005 to **0.039 mg N/L** (pH 6.0-7.0) Inhibitory to NOB → Blackburne et al. (2007)
 - 50% NOB inhibition at **FNA of 0.03 mg N/L**
- P-release and P-uptake but high P content in the effluent

Conclusions

- ✓ Stable PN was achieved at real mainstream conditions
- ✓ Operational conditions for PN in an SBR-AGS reactor after HRAS:
 - Bottom-fed F/D phase
 - DO in aerobic phases 2.0 mg/L
 - VER 50-60 %
 - HRT 12-13 h
 - Minimum SRT to foster nitrification and maximum 27 ± 15 d
 - **FNA > 0.03 mg N/L**
- ✓ Granules not strictly necessary for PN (Period I)
- ✓ Granules reduced influent-biomass- NO_2^- contact and denitrification

Publication derived from Chapters 4 and 5

Carbó et al. (2024)

<https://doi.org/10.1016/j.jwpe.2024.105165>

Journal of Water Process Engineering 60 (2024) 105165



Achieving mainstream partial nitrification with aerobic granular sludge treating high-rate activated sludge effluent

Oriol Carbó ^{a,b}, Jaume Teixidó ^b, Joan Canals ^b, Antonio Ordóñez ^b, Albert Magrí ^a, Mercè Baldi ^b, Belén Gutiérrez ^b, Jesús Colprim ^{a,*}

^a LEQUIA, Institute of the Environment, University of Girona, Campus Montilivi, Carrer Maria Aurèlia Capmany 69, 17003 Girona, Catalonia, Spain

^b GS Inima Environment, S.A., c/ Gobelos 41 1^a, 28023 Madrid, Spain



RESULTS AND DISCUSSION


4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX[®] vs. CAS

Motivation



PN control development and **assessment** with variability

Study the **performance** of the reactor

- Anammox **activity**
- **Role** of heterotrophic denitrification

Suitable effluent quality? **TN < 8 mg/L** (EU limit)


PN control strategy

- NH_4^+ and $\text{NO}_2^- + \text{NO}_3^-$ (NO_x^-) sensors installation
- Controlled variable: $\text{NO}_2^-/\text{NH}_4^+$ Ratio
- Measured variable: NH_4^+
- Manipulated variable: **aeration**


Control steps (aeration phase)

- i. Identification of NH_{4_MAX} and calculation of NH_{4_END} to achieve the setpoint $\text{NO}_2^-/\text{NH}_4^+$ Ratio
- ii. When NH_{4_END} is reached, air off

$$\text{NH}_{4_END} = \frac{\text{NH}_{4_MAX}}{1 + \text{Ratio}}$$





NO_x^- sensor only monitors




Anammox reactor operation

- ❑ Stable reactor TSS (despite not wasting): **11.6 ± 1.3 g TSS/L** (VSS/TSS 94%)
 - No accumulation
 - No washout
- ❑ Granular sludge, **TSS < 0.5 mm** less than **6 %**



✓ Correct solid-liquid separation

Anammox reactor operation



Phase I (control OFF)

- Inf. $\text{NO}_2^-/\text{NH}_4^+ > 2.5$
- ✓ Zero eff. NO_2^- and NO_3^-
- Het. denitrification**

Phase II (control OFF)

- Inf. $\text{NO}_2^-/\text{NH}_4^+ 0.5 \pm 0.3$
- Eff. $\text{NH}_4^+ 14 \pm 8$ mg N/L
- ✓ Zero eff. NO_2^- and NO_3^-

Phase III (control ON)

- Inf. $\text{NO}_2^-/\text{NH}_4^+ 1.0 \pm 0.5$
- ✓ Eff. $\text{NH}_4^+ 3.2 \pm 2.9$ mg N/L
- ✓ Zero eff. NO_2^- and NO_3^-


Anammox reactor operation

6. MAINSTREAM AUTOTROPHIC N REMOVAL FROM PN-AGS

MasterClass
patrocinada por:



Operation continues...



- Correct effluent quality, TN < 8 mg N/L
- Few instabilities



Conclusions

PN control

- ✓ A suitable strategy to control a desired effluent $\text{NO}_2^-/\text{NH}_4^+$ ratio was achieved.

Anammox

- ✓ **Coexistence** of anammox and het. denitrifiers helped **polishing** effluent NO_2^- and NO_3^- .
- ✓ Effluent suitable quality (**TN < 8 mg/L**) was achieved with $\text{AMX}_{\text{INFLUENT}}$ **$\text{NO}_2^-/\text{NH}_4^+$ of 0.80** or higher.

1

2

3

4

5

6

**7. ENERGY BALANCE:
PROGRAMOX® vs. CAS**

8

RESULTS AND DISCUSSION


4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS


6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX® vs. CAS

PROGRAMOX® vs. EDAR La Garriga: kWh/m³?



■ **La Garriga** ■ **PROGRAMOX®**



Configuración **PROGRAMOX®**:

- Consumo total **23%** inferior
 - **La Garriga**: 0.560 kWh/m³
 - **PROGRAMOX®**: 0.434 kWh/m³
- **84%** mayor recuperación energía CH₄
- Consumo balanceado **44%** inferior
 - **La Garriga**: 0.466 kWh/m³
 - **PROGRAMOX®**: 0.260 kWh/m³



✓ **Eficiencia**

1. Introduction

2. Objectives

3. Methodology

RESULTS AND DISCUSSION

4. Aerobic granulation from HRAS

5. Mainstream partial nitrification with AGS

6. Mainstream autotrophic N removal from PN-AGS effluent

7. Energy balance: PROGRAMOX® vs. CAS

8. GENERAL CONCLUSIONS

General conclusions

4. Aerobic granulation from HRAS

- ✓ Strategy to achieve AGS from HRAS effluent: selective wasting from the top of the settled sludge bed.
- ✓ Low SVI (< 100 mL/g, densified biomass) helpful enough for an improved operation with COD removal.

5. Mainstream partial nitrification with AGS

- ✓ Stable PN achieved at real mainstream conditions. Operational conditions were determined.

6. Mainstream autotrophic N removal from PN-AGS effluent

- ✓ A controlled PN-AGS effluent $\text{NO}_2^-/\text{NH}_4^+$ ratio was achieved despite flow/concentration fluctuations.
- ✓ Anammox effluent suitable quality was achieved with coexistence of anammox and het. denitrifiers.

7. Energy balance: PROGRAMOX® vs. CAS

- ✓ Significant energy saving could be reached if PROGRAMOX® was installed in La Garriga WWTP with AD.

Current/future work...

First **full-scale** PROGRAMOX® **demonstration** plant

❑ From 1.5 m³/d to 400 m³/d

PRIMA programme (EU funding)

❑ **SPORE-Med** project

July 2024 – July 2027

<https://www.spore-med.eu/>

EDAR Terrassa

❑ Place: old physicochemical

✓ Drawings done

✓ Construction done

➤ Start-up this summer



Gracias por vuestra atención.

Y muchas gracias



III Ciclo de 20 MasterClass

AGUASRESIDUALES.INFO